

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,

(SIXTH STANDARD PARALLEL SOUTH),

OF

TOWNSHIP 30 SOUTH, RANGE 2 WEST

AND

A PORTION OF THE SUBDIVISIONAL LINES,

A PORTION OF THE SUBDIVISION OF SECTION 26,

AND

THE SUBDIVISION OF SECTIONS 3, 4, 9, 11, 14, 15, 16, 22 AND 23,

IN

TOWNSHIP 31 SOUTH, RANGE 2 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Baugh
Supervisory Cadastral Surveyor

Under special instructions dated **April 15, 2005**, approved **April 15, 2005**, which provided for the surveys included under Group Number **1007**, and assignment instructions dated **April 15, 2005** and reassignment instructions dated **July 1, 2008**.

Survey commenced **April 18, 2005**
Survey completed **December 13, 2005**

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,

(SIXTH STANDARD PARALLEL SOUTH),

OF

TOWNSHIP 30 SOUTH, RANGE 2 WEST

AND

A PORTION OF THE SUBDIVISIONAL LINES,

A PORTION OF THE SUBDIVISION OF SECTION 26,

AND

THE SUBDIVISION OF SECTIONS 3, 4, 9, 11, 14, 15, 16, 22 AND 23,

IN

TOWNSHIP 31 SOUTH, RANGE 2 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Baugh
Supervisory Cadastral Surveyor

Under special instructions dated **April 15, 2005**, approved **April 15, 2005**, which provided for the surveys included under Group Number **1007**, and assignment instructions dated **April 15, 2005** and reassignment instructions dated **July 1, 2008**.

Survey commenced **April 18, 2005**
Survey completed **December 13, 2005**

INDEX DIAGRAM

Township 31 South, Range 2 West

		6	4	3	
6	5 24	4 19 23	3 15	2 14	1
7	8 22	9 19 22	10	11 9 14	12
18	17 21	16 18 20	15 12 16	14 8 11	13
19	20	21 17	22 11 16	23 7 10	24
30	29	28	27 10	26	25
31	32	33	34	35	36

The Dependent Resurvey of a Portion of the Subdivision
of Section 26.....Page 25

The Subdivision of Section 3.....Page 26
The Subdivision of Section 4.....Page 27
The Subdivision of Section 9.....Page 28
The Subdivision of Section 11.....Page 29
The Subdivision of Section 14.....Page 31
The Subdivision of Section 15.....Page 33
The Subdivision of Section 16.....Page 34
The Subdivision of Section 22.....Page 37
The Subdivision of Section 23.....Page 39

T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the south boundary, T. 30 S., R. 2 W. (Sixth Standard Parallel South), and a portion of the subdivisional lines, a portion of the subdivision of section 26, and the subdivision of sections 3, 4, 9, 11, 14, 15, 16, 22 and 23, T. 31 S., R. 2 W., Salt Lake Meridian, Utah.

History of Surveys

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY			
Portion	T.C. Bailey	1876	
All	Thoma and Bunbury	1913-15	Thoma and Bunbury 1913-15
Portion			L.V. Judd 1997
EAST BOUNDARY			
Portion	Bailey and Burrill	1874	
All	Thoma and Bunbury	1913-15	Thoma and Bunbury 1913-15.
WEST BOUNDARY			
All	Thoma and Bunbury	1913-15	
NORTH BOUNDARY (Sixth Standard Parallel South)			
Portion	Bailey and Burrill	1874	
Portion	Brecken and Mc Carty	1897	
Portion	J.P. Walker	1904	J.P. Walker 1904
Portion			Thoma and Bunbury 1913-15
SUBDIVISION			
Portion	T.C. Bailey and J.G. Burrill	1874	
Portion	T.C. Bailey	1876	
Portion	Thoma and Bunbury	1913-15	Thoma and Bunbury 1913-15
Portion			R.C. Yundt 1949
Portion			L.V. Judd 1996
Portion			L.V. Judd 1997
REMONUMENTATION			
Portion			F. Reynolds 1972

T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1007, dated April 15, 2005.

The directions of the lines were determined by mean geodetic inverse between corners. Global Positioning System (GPS) utilizing Real-time kinematics (RTK) was used throughout the survey. Cadastral Measurement Management (CMM) was utilized during the course of the survey.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the 1/4 section corner of sections 10 and 11, T. 31 S., R. 2 W., as determined by a tie to the National Geodetic Survey Control Station "ANTIMONY" utilizing GPS, using RTK techniques, is as follows:

Latitude: 38°07'26.679" N. Longitude: 111°59'12.311" W.
N.A.D. 1983, Network Accuracy=0.200 meters at 95% confidence.

The geographic position of National Geodetic Survey Control Station "ANTIMONY" is as follows:

Latitude: 38°07'02.66298" N. Longitude: 111°58'48.15386" W.
N.A.D. 1983 (1994), N.A.V.D. 1988 6973 feet.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
 (SIXTH STANDARD PARALLEL SOUTH),
 T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the South Boundary,
 (Sixth Standard Parallel South)
 T. 30 S., R. 2 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
 Bailey and Burrill in 1874 and Resurveyed by
 Thoma and Bunbury in 1913

Beginning at the standard 1/4 section corner of section 35,
 monumented with a malapai stone 20x12x7 inches, (record is flint
 stone 20x12x7 with no reference mound), firmly set and clearly
 marked 1/4 on the north face, with a reference mound of stone to
 the north.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20
 inches in the ground, and in a mound of stone, 3 1/2 foot base
 to top, with aluminum cap marked:

SC
 T30S R2W
1/4 S35
 2005

Bury the marked stone along the southeast side of aluminum post.

Corner is located on gradual north slope of mesa top.

S. 89°27.2' W., along the south boundary of section 35.

Over gentle rolling land.

37.105

The closing corner of sections 2 and 3, T. 31 S., R. 2 W.,
 monumented with a malapai stone 17x11x8 inches (record; flint
 stone 12x11x8 inches), firmly set and clearly marked 6 notches
 on the south, 2 notches on the east, and 4 notches on the west
 edges, with a reference mound of stone to the south.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20
 inches in the ground to bedrock, over a magnet, and in a mound
 of stone, 3 foot base to top, with aluminum cap marked:

S35

S3	S2
C	C

T31S R2W
 2005

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
 (SIXTH STANDARD PARALLEL SOUTH),
 T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Bury marked stone alongside the aluminum post.

Set a steel fence post alongside aluminum post.

Corner is located on gradual north slope in scattered sagebrush.

40.797

The standard corner of sections 34 and 35, monumented with a flint stone 18x10x10 inches, firmly set, projecting 10 inches above ground, clearly marked 2 notches on the east edge, 4 notches on the west edge, and 6 notches on the north edge, a reference mound of stone to the west, and a steel fence post, bears S. 40° W., 15 feet distance.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 21 inches in the ground, with magnet at base, and in a mound of stone, 3 ft. base to top, with aluminum cap marked:

SC
T30S R2W
S34 S35
— —
2005

Bury the marked stone alongside the aluminum post.

Corner is located on a gentle north slope of mesa top.

Reestablishment of the Survey Executed by
 Bailey and Burrill in 1874

S. 89°22.0' W., along the south boundary of section 34.

Over gentle rolling land.

20.363

Point for the standard E 1/16 section corner of section 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, and in a collar of stone, 3 foot base to top, with aluminum cap marked:

SC
E 1/16 S34
— —
2005

37.478

Point for the 1/4 section corner of section 3 only, at midpoint between the closing corners of sections 2 and 3 and sections 3 and 4, T. 31 S., R. 2 W.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
 (SIXTH STANDARD PARALLEL SOUTH),
 T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, and in a collar of stone, with aluminum cap marked:

1/4 S3
 T31S R2W
 2005

Corner is located on a flat in sagebrush, 20 feet south of a shallow draw, drains west.

- 40.726** Point for the standard 1/4 section corner of section 34, at proportionate distance; there is no remaining evidence of the original corner. Not monumented.
- 78.648** The true point for the closing corner of sections 3 and 4, T. 31 S., R. 2 W., hereinafter described.
- 81.452** The standard corner of sections 33 and 34, T. 30 S., R. 2 W., monumented with a granite stone 12x8x5 inches, firmly set in irrigated pasture, dimly marked and in an old fence line, bears E and W.

From which the original ties

The north point of mountains on south side of canyon,
 bears N. 81° W.

West point of rocky crowned hill in valley,
 bears N. 18 1/2° E.

White faced mountain in the rim of the basin,
 bears S. 6 1/4° E.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

SC
 T30S R2W
 S33 | S34
 ———
 T31S
 2005

Deposit the marked stone alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
 (SIXTH STANDARD PARALLEL SOUTH),
 T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89°18.1' W., along the south boundary of section 33.

Over swampy pasture land.

- 38.054** Point for the 1/4 section corner of section 4 only, T. 31 S., R. 2 W., at midpoint between the closing corners of sections 3 and 4, and sections 5 and 6, falls in large swampy area. Not monumented.
- 40.578** Point for the standard 1/4 section corner of section 33, at proportionate distance, falls in swampy pasture land; there is no remaining evidence of the original corner. Not monumented.
- This point is under water during flooding of the E. Fork of the Sevier River and throughout the summer months when under irrigation.
- 58.483** True point for the W 1/16 section corner of section 4 only, T. 31 S., R. 2 W., is at midpoint on the north boundary of section 4, between the 1/4 section corner of section 4 and the closing corner of sections 4 and 5, falls in flood plain of the East Fork of the Sevier River and at flood stage is impractical to monument.
- 63.073** Point selected for the witness corner to the W 1/16 section corner of section 4, T. 31 S., R. 2 W.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, over a magnet, and in a collar of stone, with aluminum cap marked:

WC
 →
 W 1/16 S4
 2005

Corner is located on east slope in scattered sagebrush.

- 78.912** The closing corner of sections 4 and 5, T. 31 S., R. 2 W., hereinafter described.
- 81.156** The standard corner of sections 32 and 33, monumented with a sandstone 16x10x8 inches, firmly set, 8 inches above ground, clearly marked 4 notches on the east edge, 2 notches on the west edge, and 6 notches on the north edge, and a reference mound of stone to the north.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a collar of stone, 3 foot base to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
 (SIXTH STANDARD PARALLEL SOUTH),
 T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

SC
 T30S R2W
 S 32 | S 33
 ————
 2005

Bury the marked stone alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional Lines,
 T. 31 S., R. 2 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
 Bailey and Burrill in 1874

From the 1/4 section corner of sections 23 and 24, monumented with a recorded rebar, 5/8 inch diameter, projecting 2 inches above ground, with yellow plastic cap in poor condition, with no visible marks. This monument has been recorded in File No. 522, Garfield County Recorders office on November 17, 2003 and is accepted as a careful and faithful reestablishment of the corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, and in a mound of stone, 3 foot base to top, with aluminum cap marked:

T31S R2W
 1/4
 S23 | S24
 2005

Bury rebar and plastic cap inside aluminum post.

Corner is located 7 feet west of fence, which bears NE and SW.

N. 1°32.8' W., between sections 23 and 24.

Over gentle rolling land.

20.134

The N 1/16 section corner of sections 23 and 24, monumented with a rebar, 5/8 inch diameter, firmly set, projecting 3 inches above ground, with plastic cap marked PLS 343639 (Trevor R. Gadd), as recorded in File No. 522, Garfield County Recorder's office on November 17, 2003, and is accepted as a careful and faithful determination of the corner point.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, over a magnet, and in a mound of stone, 3 foot base to top, with aluminum cap marked:

N 1/16
S23 | S24
2005

Bury rebar and plastic cap inside the aluminum post.

Corner is located on a south slope in sagebrush and 35 feet north of a dirt road, which bears E and W.

N. 1°32.9' W., beginning new measurement.

20.139 The corner of sections 13, 14, 23 and 24, monumented with a granite stone 14x8x7 inches, firmly set, and clearly marked with 1 groove on east and 4 grooves on south faces.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over magnet, 26 inches in the ground, with aluminum cap marked:

T31S R2W
S14 | S13

S23 | S24
2005

Bury the marked stone along north side of aluminum post.

Corner is located on north slope, in sagebrush, approximately 60 feet south of draw, draining West.

N.1°33.9' W., between sections 13 and 14.

Over rolling land.

39.933 The 1/4 section corner of sections 13 and 14, monumented with a granite stone 14x9x6 inches, loosely set and clearly marked 1/4 on the west face, with a steel fence post alongside.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with magnet at base, and in a mound of stone, 3 foot base to top, with aluminum cap marked:

T31S R2W
1/4
S14 | S13
2005

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Bury the marked stone alongside the aluminum post.

Corner is located on southwesterly slope in sagebrush.

N. 0°46.2' E., beginning new measurement.

- 40.007 The corner of sections 11, 12, 13 and 14, monumented with an iron post, 2 inches diameter, firmly set, projecting 16 inches above ground, with brass cap marked as described in the official record of the 1913-15 resurvey, with the original marked stone along the eastside of the iron post.

Corner is located on the south side of a wash, drains SW.

Reestablishment of the Resurvey Executed by
Thoma and Bunbury in 1913-15

N. 0°10.9' W., between sections 11 and 12.

- 39.136 True point for the 1/4 section corner of section 11 only, hereinafter described.

- 40.018 The 1/4 section corner of section 12 only, determined from the remains of the reference mound of stone to the east. The corner point was determined to be the middle and on the west side of the reference mound of stone. There is no remains of the 1915 iron post.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground with 2 magnets at base, with aluminum cap marked:

T31S R2W
| 1/4
| S12
2005

Raise a mound of stone, 3 ft. base, 2 ft. high east of corner.

Corner is located on a flood plain of a wash.

N. 0°10.8' E., beginning new measurement.

- 38.055 True point for the closing corner of sections 2 and 11 hereinafter described.

- 39.892 The corner of sections 1 and 12, monumented with an iron post, 2 inches diameter, firmly set, projecting 15 inches above ground, with brass cap marked as described in the official record of the 1913-15 survey, with a steel fence post alongside.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Resurvey Executed by
Robert C. Yundt in 1945

From the 1/4 section corner of sections 26 and 27, monumented with an iron post, 1 inch diameter, firmly set, projecting 10 inches above ground, with brass cap marked as described in the official record of the 1949 resurvey.

Corner is located on a southeast slope in scattered sagebrush, 1 foot North of fence, bears E and W.

N. 1°28.1' W., between sections 26 and 27.

Over rolling land.

40.207 Point for the corner of sections 22, 23, 26, and 27, at proportionate distance; there is no remaining evidence of the original corner, falls in alfalfa field. Not monumented.

From the 1/4 section corner of sections 23 and 26, monumented with a recorded rebar, 5/8 inch diameter, firmly set, projecting 2 inches above ground, with plastic cap marked PLS 343639 (Trevor R. Gadd), as recorded in File No. 574, Garfield County Records office on September 28, 2005 and is accepted as a careful and faithful reestablishment of the original corner.

From this point

An unrecorded rebar, 5/8 inch diameter, firmly set, projecting 2 inches above ground, bears West, 0.061 chains distance. This point was set, using incorrect procedures and is not utilized during the course of this resurvey.

S. 86°29.0' W., between sections 23 and 26.

Over cultivated land.

20.074 The W 1/16 section corner of sections 23 and 26, monumented with a rebar, 5/8 inch diameter, projecting 3 inches above ground, with plastic cap marked PLS 343639 (Trevor R. Gadd),), as recorded in File No. 574, Garfield County Records office on September 28, 2005, falls on private property, no improvements made, and is accepted as a careful and faithful establishment of the corner.

S. 86°29.0' W. beginning new measurement.

20.074 The point for the corner of sections 22, 23, 26 and 27.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. $3^{\circ}13.8'$ W., between sections 22 and 23.

Over irrigated land.

40.753

Point for the 1/4 section corner of sections 22 and 23, determined by local property corner monuments, set by Jones and DeMille Engineering. The original rebar with plastic cap set by Jones and DeMille has been destroyed, due to the many improvements in this area. There are nearby recorded survey markers set by Jones and DeMille Engineering as recorded in File No. 91, Garfield County Recorder's office on July 13, 1990 that were used to reestablish this corner point. This point was not monumented, due to its location in pastureland and near an irrigation ditch.

From this point the local reference objects

A rebar, 5/8 inch diameter, firmly set, projecting 2 inches above ground, with 2 inches diameter aluminum cap marked LS 6295, bears N. $48^{\circ}07.7'$ E., 302.8 links distance.

A rebar, 5/8 inch diameter, firmly set, projecting 2 inches above ground, with 2 inches diameter aluminum cap marked LS 6295, bears N. $88^{\circ}38.3'$ E., 201.2 links distance.

from which the reference objects

A magnail in a fence post, firmly set, 6 inches diameter, 5 feet above ground, bears N. $38^{\circ}15.5'$ E., 17.0 links distance.

A magnail in a fence post, firmly set, 5 inches diameter, 5 feet above ground, bears S. $41^{\circ}28.5'$ E., 15.5 links distance.

N. $0^{\circ}43.2'$ E., beginning new measurement.

20.067

Point for the N1/16 section corner of sections 22 and 23. Not monumented.

40.134

Point for the corner of sections 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner, falls on private ground. Not monumented.

from which the reference objects

A magnail, 1/2 inch diameter, bears S. $58^{\circ}28.0'$ E., 4.3 links distance on a cedar fence post, 4 ins. diameter.

A magnail, 1/2 inch diameter, bears S. $75^{\circ}45.2'$ W., 15.8 links distance on a cedar fence post, 4 ins. diameter.

From the corner of sections 13, 14, 23 and 24.

S. $87^{\circ}06.9'$ W., between sections 14 and 23.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

39.755

The 1/4 section corner of sections 14 and 23, monumented with a granite stone 16x11x9 inches, loosely set and dimly marked 4 on one side.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, over a magnet, and in a collar of stone, with aluminum cap marked:

T31S R2W
S14
1/4 —
S23
2005

Bury marked stone along north side of aluminum post.

Corner is located on north slope in sagebrush.

S. 89°48.3' W., beginning new measurement.

20.025

Point for the W 1/16 section corner of sections 14 and 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, over a magnet, in a collar of stone, with aluminum cap marked:

S14
W 1/16 —
S23
2005

Corner is located at base of gravel slope, 10 feet east of a fence, which bears N and S.

40.050

The point for the corner of sections 14, 15, 22 and 23.

N.1°50.5' W., between sections 14 and 15.

Over pasture land.

20.034

Point for the S 1/16 section corner of sections 14 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, over a magnet, with aluminum cap marked:

S 1/16
S15 | S14
2005

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located in pasture, and in line with fences to the east and west.

Drive a steel fence post along north side of aluminum post.

40.068

The 1/4 section corner of sections 14 and 15, monumented with a recorded rebar, 3/8 inch diameter, firmly set, projecting 4 inches above ground, with plastic cap marked RLS 183343 (Ryan W. Savage), as recorded in File No. 351, Garfield County Recorders office on December 21, 1998 and a granite stone 17x12x12 inches, clearly marked 1/4 on one side, lying alongside rebar. Rebar and plastic cap are accepted as a careful and faithful perpetuation of the original corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in collar of stone, with aluminum cap marked:

T31S R2W
1/4
S15 | S14
2005

Bury the rebar with plastic cap inside the aluminum post and the marked stone alongside the aluminum post.

Corner is located on southwest slope in sagebrush.

N. 1°26.5' W., beginning new measurement.

19.875

The N 1/16 section corner of sections 14 and 15, monumented with a rebar, 5/8 inch diameter, projecting 6 inches above ground, with plastic cap marked RLS 183343 (Ryan W. Savage), and in a collar of stone, as recorded in File No. 351, Garfield County Recorders office on December 21, 1998, and is accepted as a careful and faithful establishment of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 19 inches in the ground, in a mound of stone, 3 1/2 foot base to top, with aluminum cap marked:

N 1/16
S15 | S14
2005

Bury the rebar with plastic cap inside aluminum post.

Drive a steel fence post along west side of aluminum post.

Corner is located on NW slope in scattered sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 1°27.4' W., beginning new measurement.

- 19.905 The corner of sections 10, 11, 14 and 15, monumented with a stainless steel post, 2 1/2 inches diameter, projecting 2 inches above mound of stone, with brass cap marked as described in the official record of the 1996 dependent resurvey.

Corner is located on southwest slope in sagebrush.

From the corner of sections 11, 12, 13 and 14.

S. 88°25.4' W., between sections 11 and 14.

- 40.756 Point for the 1/4 section corner of sections 11 and 14, at proportionate distance; there is no remaining evidence of the 1913-15 iron post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with aluminum cap marked:

T30S R2W
S11
1/4 ———
S14
2005

Raise a mound of stone, 3 ft. base, 2 ft. high north of corner.

- 61.134 Point for the W 1/16 section corner of sections 11 and 14. Not monumented.

- 81.512 The corner of sections 10, 11, 14 and 15.

From the corner of sections 2, 3, 10 and 11, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with aluminum cap marked as described in the official record of the 1996 resurvey.

N. 89°55.5' E., between sections 2 and 11.

- 40.081 The 1/4 section corner of sections 2 and 11, monumented with a trachyte, 6X6X11 inches, firmly set, clearly marked 1/4 on north face, with a reference mound of stone to the north.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground with magnet at base, in a mound of stone, 3 feet base, to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T31S R2W
S2
1/4 —
S11
2005

Bury marked stone along west side of aluminum post.

Corner is located on north slope in pinyon and grass, 100 feet
South of wash, drains SW.

S. 89°54.7' E., beginning new measurement.

41.366 True point for the closing corner of sections 2 and 11 at
intersection with the West boundary of section 12. Point not
monumented.

41.384 The closing corner of sections 2 and 11, monumented with an iron
post, 2 inches diameter, firmly set, projecting 14 inches above
ground, with brass cap marked as described in the official
record of the 1913-15 survey, with a steel fence post alongside.
This monument will now function as an amended monument.

Add "AM 2005" to the cap.

From the corner of sections 2, 3, 10 and 11.

N. 0°47.7'W., between sections 2 and 3.

Over rolling hills.

40.002 The 1/4 section corner of sections 2 and 3, monumented with a
malapai stone 16x16x12 inches (record; granite stone), firmly
set and clearly marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10
inches in the ground to bedrock, in a mound of stone, 5 foot
base to top, with aluminum cap marked:

T31S R2W
1/4
S3 | S2
2005

Bury the marked stone alongside the aluminum post

Corner is located on a rocky west slope.

N. 2°42.8' E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.182

The closing corner of sections 2 and 3, hereinbefore described.

From the point for the corner of sections 22, 23, 26 and 27.

N. 89°49.9' W., between sections 22 and 27.

Over pasture land.

20.053

Point for the E 1/16 section corner of sections 22 and 27.
Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, over a magnet, with aluminum cap marked:

S22
E 1/16 —
S27
2005

Corner is located in flat pastureland, approximately 350 feet east of base of ledge, 100 feet west of East fork of Sevier River, and 120 feet south of East Fork of Sevier River.

40.106

The 1/4 section corner of sections 22 and 27, monumented with an iron post, 1 inch diameter, firmly set, projecting 4 inches above mound of stone, with a brass cap marked as described in the official record of the 1913-15 dependent resurvey of a portion of the subdivisional lines.

The bearing trees were recovered dead and fallen.

Corner is located on northeast slope in piñon and sagebrush.

From the point for the corner of sections 14, 15, 22 and 23.

S. 88°28.6' W., along the south boundary of section 15.

Over pasture land.

20.514

Point for the E 1/16 section corner of sections 15 and 22. Not monumented.

41.028

The 1/4 section corner of sections 15 and 22, monumented with a granite stone 18x12x8 inches, firmly set, projecting 10 inches above ground, clearly marked 1/4 on the north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, over a magnet, and in a mound of stone, 3 foot base to top, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T31S R2W
S15
1/4 —
S22
2005

Bury the marked stone along north side of aluminum post.

Corner is located on north slope in scattered sagebrush.

S. 88°24.4' W., beginning new measurement.

20.040 Point for the W 1/16 section corner of sections 15 and 22. Not monumented.

34.935 Point for the closing corner of sections 21 and 22, hereinafter described.

40.080 The southwest corner of section 15 only, monumented with a granite stone 20x12x10 inches, firmly set, clearly marked 3 notches on the south edge and 3 grooves on the east face, in a scattered mound of stone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 19 inches in the ground, and in a collar of stone to top, with aluminum cap marked:

T31S
R2W
S15
└─
S21
2005

Bury the marked stone along south side of aluminum post.

No remaining evidence of original bearing trees recovered.

Corner is located on gradual northeast slope in sagebrush and piñon.

From the 1/4 section corner of section 21 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 14 inches above ground, set in a mound of stone, with brass cap marked as described in the official record of the 1913-15 survey.

No remaining evidence of the original bearing tree was recovered.

N. 0° 04.7' E., on the east boundary of section 21.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

0.412

The 1/4 section corner of section 22, monumented with an iron post, 1 inch diameter, firmly set, projecting 14 inches above ground, in a mound of stone, with brass cap marked as described in the official record of the 1913-15 survey.

No remaining evidence of the original bearing tree was recovered.

39.569

The closing corner of sections 21 and 22, monumented with an iron post, 2 inches diameter, firmly set, projecting 19 inches above ground, with brass cap marked as described in the official record of the 1913-15 resurvey.

Add the marks "AM 2005" to the brass cap.

Corner is located on slight NW slope in sagebrush and scattered piñon, 30 feet East of a draw, drains NE.

39.720

Point for the closing corner of sections 21 and 22, at intersection with the south boundary of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground with magnet at base, in a mound of stone, 3 feet base, to top, with aluminum cap marked:

T31S R2W
S15

S21	S22
CC	
2005	

From the southwest corner of section 15 only.

N. 0°37.8' W., on the west boundary of section 15.

Over rolling land.

0.645

Point for the closing corner of sections 16 and 21 on the west boundary of section 15, hereinafter described.

20.112

Point for the S 1/16 section corner of sections 15 and 16. Not monumented.

40.224

The 1/4 section corner of sections 15 and 16, monumented with a granite stone 10x10x8 inches, firmly set, clearly marked 1/4 on the west face, with a reference mound to the west.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T31S R2W
1/4
S16 | S15
2005

Bury the marked stone along the east side of the aluminum post.

Raise a mound of stone west of corner.

Corner is located on north slope, at intersection of fences,
bears E and W.

N. 0°20.2' W., beginning new measurement.

- 20.040** Point for the N 1/16 section corner of sections 15 and 16. Not monumented.
- 40.080** The corner of sections 9, 10, 15, and 16, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above mound of stone, with aluminum cap marked as described in the official record of the 1996 dependent resurvey.

N. 0°34.9' W., between sections 9 and 10.

Over cultivated land.

- 36.430** The witness 1/4 section corner of sections 9 and 10, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with aluminum cap marked as described in the official record of the 1996 dependent resurvey.

Corner is located in an E - W fence line.

N. 0°34.9' W., beginning new measurement.

- 4.003** True point for the 1/4 section corner of sections 9 and 10, at proportionate distance, falls in canal and cannot be monumented.
- 44.440** The corner of sections 3, 4, 9 and 10, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, flush with ground, with aluminum cap marked as described in the official record of the 1996 dependent resurvey.

N. 0°31.3' W., between sections 3 and 4.

Over irrigated land.

- 40.194** Point for the 1/4 section corner of sections 3 and 4, at proportionate distance, falls in swampy pastureland; there is no remaining evidence of the original corner. Not monumented.
- 80.388** The closing corner of sections 3 and 4, monumented with a granite stone, 18x12x9 inches, firmly set and clearly marked

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

with 3 notches on the east and west edges, 6 notches on the north edge, and CC on the south face. No marks added to the marked stone due to its location on private property. This will now function as an amended monument.

Corner is located in an E - W fence line.

80.412 True point for the closing corner of sections 3 and 4, at the intersection with the Sixth Standard Parallel South. Point not monumented.

From the corner of sections 20 and 21, on the south boundary of section 16, monumented with an iron post, 2 inches diameter, firmly set on solid rock, in a mound of stone, with brass cap marked as described in the official record of the 1913-15 resurvey.

Corner is located on a steep north slope in ledges.

From this point, the closing corner of sections 16 and 17, monumented with an iron post, 2 inches diameter, firmly set, projecting 8 inches above ground, with brass cap marked as described in the official record of the 1913-15 resurvey, bears N. 89°53.0' W., 5.875 chains distance.

Corner is located on a steep north slope in ledges.

S. 89°57.4' E., on the south boundary of section 16.

Over broken ledges.

34.397 True point for the 1/4 section corner of section 16 only. Not monumented.

39.890 The 1/4 section corner of section 21 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 17 inches above ground, with brass cap marked as described in the official record of the 1913-15 resurvey.

Corner is located on north slope in scattered sagebrush.

S. 89°48.4' E., beginning new measurement.

34.650 The closing corner of sections 16 and 21, monumented with an iron post, 2 inches diameter, firmly set, projecting 18 inches above ground, and in a mound of stone, with brass cap marked as described in the official record of the 1913-15 dependent resurvey of a portion of the subdivisional lines.

Add the marks "AM 2005" to the brass cap.

Corner is located on gradual northeast slope in sagebrush and piñon.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS
34.697

True point for the closing corner of sections 16 and 21, at intersection with the west boundary of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, over a magnet, and in a mound of stone, 3 1/2 foot base to top, with aluminum cap marked:

	T31S R2W		
C	S16		
C	—		S15
	S21		
			2005

From the corner of sections 8, 9, 16 and 17, monumented with a granite stone 17x10x6 inches, firmly set and clearly marked 4 notches on the south and east edges, with a reference mound of stone to the west. (Record; no reference mound of stone)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to solid rock, and in a collar of stone, with aluminum cap marked:

	T31S R2W		
	S8		S9
	—		
	S17		S16
			2005

Bury marked stone on south side of aluminum post.

Rebuild reference mound of stone around aluminum post.

S. 0°07.7' W., between sections 16 and 17.

Ascend over rolling hills.

39.952

The 1/4 section corner of sections 16 and 17, monumented with an iron post, 1 inch diameter, firmly set in a mound of stone, with brass cap marked as described in the official record of the 1913-15 resurvey.

From which the 1915 bearing trees

A cedar, 11 inches diameter, bears S. 54°15' E., 5 links distance, with visible scribe marks on partially healed blaze.

A piñon, 13 inches diameter, bears S. 37°45' W., 34 links distance, with visible scribe marks on partially healed blaze.

Corner is located at confluence of draws, drains southeast.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 0°04.4' W., beginning new measurement.

38.810 The closing corner of sections 16 and 17.

From the corner of sections 9, 10, 15 and 16.

S. 89°28.4' W., between sections 9 and 16.

Over pasture land.

19.907 Point for the E 1/16 section corner of sections 9 and 16. Not monumented.

39.814 The 1/4 section corner of sections 9 and 16, monumented with an aluminum post, 2 inches diameter, firmly set, projecting 4 inches above ground, with aluminum cap marked:

GARFIELD COUNTY SURVEYOR

T31S R2W

1/4 S9

S16

LS174457

2001

AL BARKER

LS 161040

A mound of stone, 3 foot base, 1 1/2 foot high, north of corner.

This corner is recorded in File No. 449, Garfield County Records office on October 4, 2001 and is accepted as a careful and faithful reestablishment of the original corner position.

From the corner point, an unrecorded rebar, 1/2 inch diameter, firmly set, projecting 5 inches above ground, at intersection of fences, bearing N and E, bears S. 35°08.3' W., 0.700 chs. distance, set using incorrect procedures and is not utilized during the course of this resurvey.

S. 89°28.5' W., beginning new measurement.

39.826 The corner of sections 8, 9, 16, and 17.

N. 0°21.2' W., between sections 8 and 9.

Over rolling hills.

40.174 The 1/4 section corner of sections 8 and 9, monumented with a granite stone 12x12x6 inches, firmly set, clearly marked 1/4 on the west face and a reference mound of stone to the east.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 inches long 2 1/2 inches diameter, 24 inches in the ground, over a magnet, and in a collar of stone, with aluminum cap marked:

T31S R2W
1/4
S8 | S9
2005

Bury the marked stone alongside the aluminum post.
Drive a steel fence post alongside the aluminum post.

Corner is located on gradual east slope and in sagebrush.

N. 2°02.9' W., beginning new measurement.

40.516

The corner of sections 4, 5, 8 and 9, monumented with a sandstone 17x10x10 inches, firmly set, projecting 6 inches above ground, clearly marked with 5 notches on the south and 4 notches on the east edges, and a steel fence post to the west.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

T31S R2W
S5 | S4
—+—
S8 | S9
2005

Bury the marked stone alongside the aluminum post.

Raise a mound of stone west of the corner.

Corner is located on gradual northeast slope in sagebrush and scattered piñon.

From the corner of sections 3, 4, 9 and 10.

S. 88°51.1' W., between sections 4 and 9.

40.244

The 1/4 section corner of sections 4 and 9, monumented with an aluminum post, 2 inches diameter, firmly set, projecting 3 inches above ground, with aluminum cap marked:

GARFIELD COUNTY SURVEYOR
T31S R2W
1/4 S4
—+—
S9
LS174457
2001

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

This corner is recorded in File No. 449, Garfield County
Recorders office on October 4, 2001 and is accepted as a careful
and faithful reestablishment of the original corner position.

S. 89°49.0' W., beginning new measurement.

Over rolling land.

20.125 Point for the W 1/16 section corner of sections 4 and 9.

Corner not monumented.

40.250 The corner of sections 4, 5, 8 and 9.

N. 2°33.5' W., between sections 4 and 5.

Over rolling land.

20.150 Point for the S 1/16 section corner of sections 4 and 5. Not
monumeted.

40.300 Point for the 1/4 section corner of sections 4 and 5, at
proportionate distance, utilizing irregular boundary adjustment;
there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 15
inches in the ground, over a magnet, and in a mound of stone, 3
1/2 foot base to top, with aluminum cap marked:

T31S R2W
1/4
S5 | S4
2005

Corner is located on east slope in sagebrush.

N. 0°15.0' W., beginning new measurement.

40.092 True point for the closing corner of sections 4 and 5, at
intersection with, Sixth Standard Parallel South.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter,
over a magnet, 22 inches in the ground, and in a collar of
stone, with aluminum cap marked:

T30S R2W
S33
S5 | S4
CC
T31S
2005

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on east slope in sagebrush.

40.410

The closing corner of sections 4 and 5, monumented with a malapai stone 16x10x8 inches, loosely set in mound of stone, clearly marked 4 notches on the east and 2 notches on the west edges, CC on the south face. Add the marks AM on south face and bury the stone in place, 6 inches below surface.

Dependent Resurvey of a Portion of the Subdivision of Section 26,
T. 31 S., R. 2 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
R.C. Yundt in 1949

Note: The 1/4 section corner of sections 23 and 26 was reestablished by R.C. Yundt in 1949 by identification by Charles A. Riddle of Antimony, Utah, as being long used as the corner and to which the surrounding property lines are referenced. Subsequent to 1949, the iron post has been lost. In 2005, the 1/4 section corner of sections 23 and 26 and the corner of sections 22, 23, 26 and 27 were reestablished by Trevor R. Gadd, Utah Land Surveyor Number 343639, as recorded in File No. 574, Garfield County Recorders office on September 28, 2005. The determination was made that a portion of the subdivision of section 26 needed to be resurveyed to verify that the 1/4 section corner of sections 23 and 26, reestablished by Trevor R. Gadd, Utah Land Surveyor 343639 was reestablished using correct procedures and was in agreement with the survey of the subdivision of section 26 by R.C. Yundt in 1949.

From the center S 1/16 section corner of section 26, monumented with an iron post, 1 inch diameter, firmly set, projecting 14 inches above ground, with brass cap marked as described in the official record of the 1949 survey.

Corner is located on northeast slope in sagebrush, at intersection of fences bearing South and West.

N. 1°49.6' W., on the N - S center line of section 26.

20.147

The center 1/4 section corner of section 26, monumented with an iron post, 1 inch diameter, firmly set, projecting 4 inches above ground, with brass cap marked as described in the official record of the 1949 survey, with a steel fence post alongside.

Corner is located in a fence, bears N - S.

N. 1°46.1' W., beginning new measurement.

20.788

The center N 1/16 section corner of section 26, monumented with a recorded rebar, 5/8 inch diameter, firmly set, projecting 3 inches above ground, with plastic cap marked PLS 343639 (Trevor

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 26,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

R. Gadd), recorded in File No. 574, Garfield County Records office on September 28, 2005 and is accepted as a careful and faithful establishment of the corner. Not remonumented.

N. 1°46.4' W., beginning new measurement.

- 20.783** The 1/4 section corner of sections 23 and 26. Note: The overall distance of 41.571 chains (1949 record; 41.56 chains) from the center 1/4 section corner of section 26 to the 1/4 section corner of sections 23 and 26 is 0.011 chains long. This difference is within limits of the 1949 survey record. The 1/4 section corner of sections 23 and 26, reestablished by Trevor R. Gadd, Utah Land Surveyor 343639, is accepted as a faithful and careful reestablishment of the 1949 corner; hereinbefore described.

Subdivision of Section 3,
T. 31 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 3 and 10, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above mound of stone, with aluminum cap marked as described in the official record of the 1996 dependent resurvey.

N. 0°14.0' E., on the N - S center line of section 3.

- 0.09** Intersect a fence, bears N. 86° E. and S. 86° W.

- 40.225** Point for the center 1/4 section corner of section 3, at intersection with the E - W center line of section 3.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, and in a collar of stone, with aluminum cap marked:

T31S R2W
C 1/4 S3
2005

Corner is located on gradual west slope in weeds and gravel bed, approximately 350 feet south of old potato cellar.

- 47.25** Intersect potato shed, bears NE.

- 80.394** The 1/4 section corner of section 3 only, on the south boundary of section 34, T. 30 S., R. 2 W., hereinbefore described.

From the 1/4 section corner of sections 2 and 3.

S. 89°17.9' W., on the E - W center line of section 3.

Over gentle rolling land.

SUBDIVISION OF SECTION 3,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.435

The center 1/4 section corner of section 3.

80.078

The point for the 1/4 section corner of sections 3 and 4.

Subdivision of Section 4,
T. 31 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 4 and 9.

N. 0°57.9' W., on the N - S center line of section 4.

20.287

Point for the center S 1/16 section corner of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

C
S 1/16 | S4
C
2005

Set a wooden plank, 2x4x60 inches, along north side of aluminum post.

Corner is located on grassy flat ground, 155 feet west of East Fork of Sevier River, flows NW, 15 feet north of E - W fence, and 42 feet east of base of ledge.

40.574

Point for the center 1/4 section corner of section 4, at intersection with the E - W center line. Not monumented.

80.729

The point for the 1/4 section corner of section 4 only, on the south boundary of section 33, T. 30 S., R. 2 W., hereinbefore described.

From the point for the 1/4 section corner of sections 3 and 4.

S. 89°23.8' W., on the E - W center line of section 4.

Over grassy pasture land.

40.551

The point for the center 1/4 section corner of section 4.

61.232

Point for the center W 1/16 section corner of section 4.
Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 25 inches in the ground, in a mound of stone, 3 feet base, to top, with aluminum cap marked:

W 1/16
C ——— C
S4
2005

SUBDIVISION OF SECTION 4,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Corner is located on flat ground in scattered sagebrush.

81.913 The 1/4 section corner of sections 4 and 5.

From the point for the W 1/16 section corner of sections 4 and 9.

N. 1°45.5' W., on the N - S line of the SW 1/4 of section 4.

Over rolling land.

20.217 Point for the SW 1/16 section corner of section 4, at intersection with the E - W center line of the SW 1/4 of section 4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

SW 1/16 X S4
2005

Corner is located in sagebrush 16 feet south of E-W fence line.

40.434 The center W 1/16 section corner of section 4.

From the center S 1/16 section corner of section 4.

S. 89°35.9' W., on the E-W center line of the SW 1/4 of section 4.

Over pasture land.

20.403 The SW 1/16 section corner of section 4.

40.806 The point for the S 1/16 section corner of sections 4 and 5.

From the center W 1/16 section corner of section 4.

N. 0°36.5' W., on the N - S center line of the NW 1/4 of section 4.

Over nearly level land.

40.123 True point for the W 1/16 section corner of section 4 only, on the south boundary of section 33, T. 30 S., R. 2 W.

Subdivision of Section 9,
T. 31 S., R. 2 W., Salt Lake Meridian, Utah

SUBDIVISION OF SECTION 9,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 9 and 16.

N. 0°53.9' W., on the N - S center line of section 9.

Over rolling hills.

- 40.305** Point for the center 1/4 section corner of section 9, at intersection with the E - W center line of section 9.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, and in a collar of stone, with aluminum cap marked:

T31S R2W
C 1/4 S9
2005

Corner is located on gentle southeast slope, 5 feet north of E - W fence and approximately 30 feet east of N - S fence.

- 80.435** The 1/4 section corner of sections 4 and 9.

From the true point for the 1/4 section corner of sections 9 and 10.

S. 89°17.4' W., on the E - W center line of section 9.

Over pasture land.

- 20.017** The center E 1/16 section corner of section 9, monumented with a rebar, 5/8 inch diameter, firmly set, projecting 2 inches above ground, with plastic cap marked GRIMSHAW LS 174457 with a steel fence post alongside, as recorded in File No. 449, Garfield County Records office on October 4, 2001, and is accepted as a careful and faithful establishment of the corner. Not remonumented.

S. 89°17.1' W., beginning new measurement.

- 20.013** The center 1/4 section corner of section 9.

- 59.451** The 1/4 section corner of sections 8 and 9.

Subdivision of Section 11,
T. 31 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 11 and 14.

N. 0°27.8' W., on the N - S center line of section 11.

SUBDIVISION OF SECTION 11,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

- 19.805** Point for the center S 1/16 section corner of section 11. Not monumented.
- 39.610** Point for the center 1/4 section corner of section 11, at intersection with the E - W center line of section 11. Not monumented.
- 79.257** The 1/4 section corner of sections 2 and 11.

From the 1/4 section corner of section 11, monumented with an iron post, 1 inch diameter, firmly set, projecting 13 inches above ground, with brass cap marked as described in the official record of the 1913-15 resurvey. This monument will now function as an amended monument, add "AM 2005" to the cap.

S. 89°05.7' W., on the E - W center line of section 11.

- 0.088** True point for the east 1/4 section corner of section 11, at the intersection with the west boundary of section 12.
- 41.027** The point for the center 1/4 section corner of section 11.
- 61.240** The center W 1/16 section corner of section 11, monumented with an unrecorded rebar, 5/8 inch diameter, firmly set, projecting 2 inches above ground, with plastic cap marked PLS 183343 (Ryan K. Savage), and is accepted as a careful and faithful establishment of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a collar of stone, with aluminum cap marked:

W 1/16
C ————— C
S11
2005

Bury rebar and plastic cap inside aluminum post.

Corner is located on a flat in sagebrush and weeds.

S. 89°04.1' W., beginning new measurement.

- 20.201** The 1/4 section corner of sections 10 and 11, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with aluminum cap marked as described in the official record of the 1996 resurvey.

From this point, National Geodetic Survey control point "ANTIMONY" bears S. 38°28'26" E. (forward bearing) and N. 38°28'11" W. (reverse bearing), 47.031 chains distance.

SUBDIVISION OF SECTION 11,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the W 1/16 section corner of sections 11 and 14.

N. 0°14.0' W., on the N - S center line of the SW 1/4 of section 11.

- 19.925** The SW 1/16 section corner of section 14, monumented with an unrecorded rebar, 5/8 inch diameter, firmly set, 2 inches below ground, with plastic cap marked PLS 183343 (Ryan K. Savage), and is accepted as a careful and faithful establishment of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, in a collar of stone, with aluminum cap marked:

SW 1/16 X S 11
2005

Bury rebar and plastic cap inside aluminum post.

N. 0°14.0' W., beginning new measurement.

- 19.925** The center W 1/16 section corner of section 11.

From the point for the center S 1/16 section corner of section 11.

S. 88°45.9' W., on the E - W center line of the SW 1/4 of section 11.

- 20.295** The SW 1/16 section corner of section 11.

S. 88°44.9' W., beginning new measurement.

- 20.287** The S 1/16 section corner of sections 10 and 11, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, with aluminum cap marked as described in the official record of the 1996 resurvey.

Subdivision of Section 14,
T. 31 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 14 and 23.

N. 1°08.0' W., on the N - S center line of section 14.

SUBDIVISION OF SECTION 14,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

20.468 Point for the center S 1/16 section corner of section 14. Not monumented.

40.936 Point for the center 1/4 section corner of section 14, at intersection with the E - W center line of section 14. Not monumented.

80.813 The 1/4 section corner of sections 11 and 14.

From the 1/4 section corner of sections 13 and 14.

S. 88°33.6' W., on the E - W center line of section 14.

39.431 The point for the center 1/4 section corner of section 14.

59.700 Point for the center W 1/16 section corner of section 14. Not monumented.

79.969 The 1/4 section corner of sections 14 and 15.

From the W 1/16 section corner of sections 14 and 23.

N. 1°29.0' W., on the N - S center line of the SW 1/4 of section 14.

20.252 Point for the SW 1/16 section corner of section 14, at intersection with the E - W center line of the SW 1/4 of section 14, falls in fence, bears N. 2° W. and S. 2° E.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground with magnet at base, in a mound of stone, 3 feet base, to top, with aluminum cap marked:

SW 1/16 X S14
2005

From this point, an unrecorded rebar, 1/2 inch diameter, firmly set, projecting 14 inches above ground, at intersection of fences, bearing S and W, bears N. 2°24.9' W., 0.235 chains distance, set using incorrect procedures and is not utilized during the course of this resurvey.

40.499 The point for the center W 1/16 section corner of section 14.

From the point for the center S 1/16 section corner of section 14.

S. 89°10.9' W., on the E - W center line of the SW 1/4 of section 14.

20.145 The SW 1/16 section corner of section 14.

SUBDIVISION OF SECTION 14,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.290

The S 1/16 section corner of sections 14 and 15.

Subdivision of Section 15,
T. 31 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 15 and 22.

N. 0°43.4' W., on the N - S center line of section 15.

Over rolling land.

20.062 Point for the center S 1/16 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 28 inches in the ground, with aluminum cap marked:

C
S 1/16 | S15
C
2005

Set a steel fence post alongside the aluminum post.

Corner is located in pasture, 25 feet north of E - W fence and 30 feet east of N - S fence line.

40.124 Point for the center 1/4 section corner of section 15, at intersection with the E - W center line. Not monumented.

60.087 Point for the center N 1/16 section corner of section 15. Not monumented.

80.050 The 1/4 section corner of sections 10 and 15, monumented with an aluminum post, 4 inches below asphalt surface with aluminum cap marked as described in the official record of the 1996 resurvey.

From the 1/4 section corner of sections 14 and 15.

S. 88°33.0' W., on the E - W center line of section 15.

Over rolling land.

20.121 Point for center E 1/16 section corner of section 15. Not monumented.

40.242 The point for the center 1/4 section corner of section 15.

60.246 Point for the center W 1/16 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

SUBDIVISION OF SECTION 15,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

W 1/16
C ——— C
S15
2005

Corner is located 1 foot east of N - S fence line and approximately 15 feet north of the intersection of fences, bears E and N - S.

80.250 The 1/4 section corner of sections 15 and 16.

From the point for the center E 1/16 section corner of section 15.

N. 1°06.5' W., on the N - S center line of the NE 1/4 of section 15.

Over pasture land.

19.922 The NE 1/16 section corner section 15, monumented with a rebar, 5/8 inch diameter, firmly set, flush with surface of ground, and in a mound of stone and brick, as recorded in File No. 351, Garfield County Recorder's office, on December 21, 1998, and is accepted as a careful and faithful establishment of the corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, in a mound of stone to top of cap, with aluminum cap marked:

NE 1/16 X S15
2005

Bury rebar inside the aluminum post.

Corner is located on a dirt bank, slopes west.

N. 1°03.4' W., beginning new measurement

19.927 The E 1/16 section corner of sections 10 and 15, monumented with an aluminum post, 4 inches below asphalt surface with aluminum cap marked as described in the official record of the 1996 resurvey.

From the N 1/16 section corner of sections 14 and 15.

S. 88°41.4' W., on the E - W center line of the NE 1/4 of section 15.

Over pasture land.

20.005 The NE 1/16 section corner of section 15.

SUBDIVISION OF SECTION 15,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. $88^{\circ}40.3'$ W., beginning new measurement.

- 19.986 The point for the center N 1/16 section corner of section 15.

From the point for the W 1/16 section corner of sections 15 and 22.

N. $0^{\circ}40.6'$ W., on the N - S center line of the SW 1/4 of section 15.

Over rolling land.

- 20.086 Point for the SW 1/16 section corner of section 15, at an intersection with the E - W center line of the SW 1/4 of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, and in a collar of stone, with aluminum cap marked:

SW 1/16 S15
2005

Corner is located on a northwest slope, 2 1/2 feet west of N - S fence and 25 feet north of fence corner, bears N and E.

- 40.172 The center W 1/16 section corner of section 15.

From the center S 1/16 section corner of section 15.

S. $88^{\circ}28.6'$ W., on the E - W center line of the SW 1/4 of section 15.

- 0.46 Intersect fence, bears N - S.

- 19.98 Intersect fence, bears N - S.

- 20.022 The SW 1/16 section corner of section 15.

- 40.043 The point for the S 1/16 section corner of sections 15 and 16.

Subdivision of Section 16,
T. 31 S., R. 2 W., Salt Lake Meridian, Utah

From the true point for the 1/4 section corner of section 16 only.

N. $0^{\circ}13.1'$ W., on the N - S center line of section 16.

SUBDIVISION OF SECTION 16,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Over rolling land.

- 0.022** The 1/4 section corner of section 16 only, monumented with an iron post, 1 inch diameter, firmly set, projecting 15 inches above ground, with brass cap marked as described in the official record of the 1913-15 resurvey. This monument will now function as an amended monument, add "AM 2005" to the cap.

Corner is located on northeast slope in sagebrush and scattered piñon.

- 39.153** Point for the center 1/4 section corner of section 16, at intersection with the E - W center line of section 16. Not monumented.

- 59.160** Point for the center N 1/16 section corner of section 16.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, with aluminum cap marked:

C
N 1/16 | S16
C
2005

Corner is located on gentle southeast slope in scattered sagebrush, and near base of knoll north of corner.

- 79.167** The 1/4 corner of sections 9 and 16.

From the 1/4 section corner of sections 15 and 16.

S. 89°34.0' W., on the E - W center line of section 16.

Over rolling land.

- 19.950** Point for the center E 1/16 section corner of section 16.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 28 inches in the ground, and in a collar of stone, with aluminum cap marked:

E 1/16
C ——— C
S16
2005

Corner is located on gentle southeast slope, approximately 66 feet north of draw, drains E.

- 39.900** The point for the center 1/4 section corner of section 16.

- 79.970** The 1/4 section corner of sections 16 and 17.

From the center E 1/16 section corner of section 16.

SUBDIVISION OF SECTION 16,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0°16.7' W., on the N - S center line of the NE 1/4 of section 16.

- 20.023 Point for the NE 1/16 section corner of section 16, at intersection with the E - W center line of the NE 1/4.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 28 inches in the ground, and in a collar of stone, with aluminum cap marked:

NE 1/16 S16
2005

- 40.045 Corner is located on flat area in thick rabbit brush and approximately 2 1/2 chains south of Pole Creek Canyon.
The point for the E 1/16 section corner of sections 9 and 16.

From the point for the N 1/16 section corner of sections 15 and 16.

S. 89°31.4' W., on the E - W center line of the NE 1/4 of section 16.

- 19.928 The NE 1/16 section corner of section 16.
39.856 The center N 1/16 section corner of section 16.

Subdivision of Section 22,
T. 31 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 22 and 27.

N. 1°56.9' W., on the N - S center line of section 22.

- 39.956 Point for the center 1/4 section corner of section 22, at intersection with the E - W center line of section 22. Not monumented.

- 59.807 Point for the center N 1/16 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

C
N 1/16 | S22
C
2005

Corner is located on east slope of spur.

- 79.658 The 1/4 section corner of sections 15 and 22.

SUBDIVISION OF SECTION 22,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the point for the 1/4 section corner of sections 22 and 23.

S. 89°04.4' W., on the E - W center line of section 22.

- 19.583** The center E 1/16 section corner of section 22, monumented with an unrecorded rebar, 5/8 inch diameter, firmly set, projecting 2 inches above ground, with aluminum cap marked LS PROP COR and illegible marks.

This point is accepted as a careful and faithful establishment of the corner point.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 28 inches in the ground, in a collar of stone, with aluminum cap marked:

E 1/16
C ————— C
S22
2005

Bury the rebar and aluminum cap inside the aluminum post.

Corner is located on a NE slope in scattered sagebrush and piñon.

S. 89°03.4' W., beginning new measurement.

- 19.586** The point for the center 1/4 section corner of section 16.
- 55.926** The 1/4 section corner of section 22 only.

From the center E 1/16 section corner of section 22.

N. 0°36.7' W., on the N - S center line of the NE 1/4 of section 22.

- 19.950** True point for the NE 1/16 section corner of section 22, at intersection with the E - W center line of the NE 1/4 of section 22, falls near the E bank of the East Fork of the Sevier River and is unsafe to monument during high water.

Set a steel fence post, 72 inches long, 48 inches in the ground.

- 39.905** The point for the E 1/16 section corner of sections 15 and 22.

From the point for the N 1/16 section corner of sections 22 and 23.

SUBDIVISION OF SECTION 22,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

S. $88^{\circ}46.1'$ W., on the E - W center line of the NE 1/4 of section 22.

- 19.781** Point selected for the witness corner to the NE 1/16 section corner of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, over a magnet, 26 inches in the ground, with aluminum cap marked:

NE 1/16
S22
W
←
C
2005

- 20.048** True point for the NE 1/16 section corner of section 22.

- 40.098** The center N 1/16 section corner of section 22.

From the E 1/16 section corner of sections 22 and 27.

N. $2^{\circ}35.5'$ W., on the N - S center line of the SE 1/4 of section 22.

- 40.355** The center E 1/16 section corner of section 22.

Subdivision of Section 23,
T. 31 S., R. 2 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 23 and 26.

N. $1^{\circ}19.0'$ W., on the N - S center line of section 23.

- 39.260** Point for the center 1/4 section corner of section 23, at intersection with the E - W center line of section 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground with magnet at base, in a mound of stone, 3 feet base, to top, with aluminum cap marked:

T31S R2W
C 1/4 X S23
2005

From this point a recorded rebar, 5/8 inch diameter, firmly set, projecting 2 inches above ground, with yellow plastic cap marked PLS 343639 (Trevor R. Gadd), as recorded in File No. 574, Garfield County Recorders office on September 28, 2005, bears S. $89^{\circ}40.8'$ W., 0.101 chains distance, set using incorrect procedures and is not utilized during the course of this survey.

SUBDIVISION OF SECTION 23,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From this same point, an unrecorded rebar, 5/8 inch diameter, loosely set, projecting 14 inches above ground, with red plastic cap with no marks visible, bears S. $3^{\circ}11.8'$ W., 0.861 chains distance, set using incorrect procedures and is not utilized during the course of this survey.

Corner is located 3 feet East of a fence, bears N - S.

- 58.887** Point for the center N 1/16 section corner of section 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground with magnet at base, in a mound of stone, 3 feet base, to top, with aluminum cap marked:

C
N 1/16 | S23
C
2005

Corner is located on a south slope in sagebrush.

- 78.514** The 1/4 section corner of sections 14 and 23.

From the 1/4 section corner of sections 23 and 24.

S. $88^{\circ}35.0'$ W., on the E - W center line of section 23.

- 19.953** Point for the center E 1/16 section corner of section 23. Not monumented.

From this point, a rebar, 5/8 inch diameter, firmly set, projecting 3 inches above ground, with yellow plastic cap marked LS 343639 (Trevor R. Gadd), recorded in File No. 522, Garfield County Records office on November 17, 2003, bears S. $89^{\circ}32.2'$ W., 0.050 chains distance, set using incorrect procedures and is not utilized during the course of this survey.

- 39.906** The center 1/4 section corner of section 23.

- 60.642** Point for the center W 1/16 section corner of section 23. Not monumented.

- 81.378** The point for the 1/4 section corner of sections 22 and 23.

From the N 1/16 section corner of sections 23 and 24.

S. $87^{\circ}51.4'$ W., on the E - W center line of the NE 1/4 of section 23.

- 39.827** The center N 1/16 section corner of section 23.

From the point for the center W 1/16 section corner of

SUBDIVISION OF SECTION 23,
T. 31 S., R. 2 W., SALT LAKE MERIDIAN, UTAH

CHAINS

section 23.

N. 0°17.3' W., on the N - S center line of the NW 1/4 of section 23.

19.840 Point for the NW 1/16 section corner of section 23, at intersection with the E - W center line of the NW 1/4 of section 23, falls in an alfalfa field and within the range of a pivot sprinkler where it is unsafe to monument. Not monumented.

25.028 Point for a witness point on line on the NS center line of the NW 1/4 of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 16 inches in the ground, with 1 1/2 inch diameter aluminum cap marked:

WP
NW ↓ 1/16 S23
2005

Witness point is located in a fence, bears S.66°E. and N.66°W.

39.685 The W 1/16 section corner of sections 14 and 23.

From the center N 1/16 section corner of section 23.

S. 89°10.8' W., on the E - W center line of the NW 1/4 of section 23.

9.319 Point for a witness point on line on the E - W center line of the NW 1/4 of section 23.

Set a rebar, 18 inches long, 5/8 inch diameter, 16 inches in the ground with 1 1/2 inches diameter aluminum cap marked:

WP
NW 1/16
←
S23
2005

20.379 The point for the NW 1/16 section corner of section 23.

40.758 Point for the N 1/16 section corner of sections 22 and 23.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
John F. Carroll	Cadastral Surveyor
Jerry L. Thomas	Cadastral Surveyor
Burke R. Williams	Natural Resource Specialist

CERTIFICATE OF SURVEY

I, **Ronald K. Baugh**, **Supervisory Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **15th day of April, 2005**, I have **executed a dependent resurvey of a portion of the south boundary Township 30 South, Range 2 West (Sixth Standard Parallel South)**, a portion of the subdivisional lines, a portion of the subdivision of section 26, and the subdivision of sections 3, 4, 9, 11, 14, 15, 16, 22 and 23, Township 31 South, Range 2 West, of the **Salt Lake Meridian**, in the State of **Utah**, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Sept. 12, 2008
Date

Ronald K. Baugh
(Supervisory Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the **dependent resurvey of a portion of the south boundary, in Township 30 South, Range 2 West (Sixth Standard Parallel South)**, a portion of the subdivisional lines, a portion of the subdivision of section 26 and the subdivision of sections 3, 4, 9, 11, 14, 15, 16, 22 and 23, in Township 31 South, Range 2 West, Salt Lake Meridian, Utah, executed by **Ronald K. Baugh, Supervisory Cadastral Surveyor**, having been critically examined and found correct, are hereby approved.

September 26, 2008
Date

Daniel W. Webb
Chief Cadastral Surveyor for Utah